

Rotating End Cap IP66 Poultry Farm Light

Livestock Barns / Refrigerator / Freezer / Vegetable Shed
Wash Station / Bakery and Confectionery



E Series Rotating End Cap
Dimmable & Non-dimmable



FEATURES

- V-shape patent design 270° aluminum radiator structure.
- Human design, lock key & switch button, 360° rotating end cap with scale, adjust angle and position.
- Low heat, less than 50°C.
- No UV or IR light radiation, no mercury or other in-organics.
- Instant "ON" to 100% brightness.
- Worldwide top dimming technology from 0.2%-100% without flickers.
- Compatible with AMB patent smart chicken farm system
- Excellent thermal efficiency.
- Works with worldwide electrical systems.
- Humidity proof, Dust proof, Shatter proof and Waterproof with IP66 better rating.
- Optimal anti-ammonia & acid for poultry industrial lighting.
- Complied with D-mark EN60598-2-24

PARAMETER



Model No.	Triac Dimmable	Power	Size (mm)	Standard Version Lumens(LM/W)
WP4E-T8-20W	N	20w	1200	130LM/W
WP4E-T8-20W-D	Y	20w	1200	120LM/W
WP5E-T8-24W	N	24w	1500	130LM/W
WP5E-T8-24W-D	Y	24w	1500	120LM/W
WP6E-T8-28W	N	28w	1800	130LM/W
WP6E-T8-28W-D	Y	28w	1800	120LM/W

Model No.	Triac Dimmable	Power	Size (mm)	Premium Version Lumens(LM/W)
WP4E-T8-20WH	N	20w	1200	150LM/W
WP4E-T8-20WH-D	Y	20w	1200	130LM/W
WP5E-T8-24WH	N	24w	1500	150LM/W
WP5E-T8-24WH-D	Y	24w	1500	130LM/W
WP6E-T8-28WH	N	28w	1800	150LM/W
WP6E-T8-28WH-D	Y	28w	1800	130LM/W

Light Source: SMD2835 0.2W
CRI: Ra>80
CCT Options: 3000K(WW) 4000K(NW) 5000K(DW) 6500K(CW)
Input Voltage:
Non-dimmable Version AC100-240V(EU) AC100-277(US)
Dimmable Version AC100-120V or AC200-240V
Viewing Angle: 270°
Tube Diameter: D28mm
Rating: IP65 & Ik08
Warranty: 5 years

INSTALLATION

